



# HSM V-Press 503 eco



## HSM V-Press 503 vertical baling press eco

Easy installation and operation make the HSM V-press 503 eco as the ideal model for small material volumes.

### Technical data

<b>Order number:</b>	6154104	<b>Bale length x Bale width x Bale height:</b>	700 x 500 x 850 mm
<b>EAN</b>	4026631073387	<b>Bale weight:</b>	50 kg
<b>Pressing power:</b>	30 kN	<b>Noise level (idle operation):</b>	ca. 96 dB(A)
<b>Specific pressing power:</b>	8,5 N/cm <sup>2</sup>	<b>Width x Depth x Height:</b>	953 x 679 x 1962 mm
<b>Voltage / Frequency:</b>	230 V / 50 Hz	<b>Weight:</b>	245 kg
<b>Cycle time when idling vacío:</b>	30 s	<b>Type of consumables:</b>	Strapping tape
<b>Volume throughput in idle operation (theor.):</b>	3,13 m <sup>3</sup> /h	<b>Press material:</b>	Plastic film, Mixed paper, Cardboard
<b>Loading aperture width x height:</b>	700 x 505 mm		

### Product information



Bale removal and transport with discharge trolley



Microprocessor controller with membrane keypad



Low installation height and small footprint



### Compresses cardboard and film

Suitable for cardboard as well as film.



### Automatic start

Automatic start of the pressing process after closing the door.



### Optimized pressing

Massive press ram and extremely robust press plate guidance.



### Double door

To fill the press, the upper half of the doors is swung to the right.




### Bell-crank lever

Bell-crank lever for quick and safe opening of the door.



### Strapping

Manual bale strapping with continuous polyester tape.



[www.tuev-sued.de/ps-zert](http://www.tuev-sued.de/ps-zert)

[www.hsm.eu](http://www.hsm.eu)

**HSM**®