HSM V-Press 504



HSM V-Press 504 vertical baling press

The entry-level model HSM V-Press 504 allows for the eco-nomical disposal of your packaging waste.

Technical data

Order number:	6151151
EAN	4026631074421
Pressing power:	40 kN
Specific pressing power:	11,2 N/cm²
Driving power:	1,1 kW
Voltage / Frequency:	230 V / 50 Hz
Cycle time when idling vacío:	27 s
Volume throughput in idle operation (theor.):	3,75 m³/h
Loading height:	661 mm
Loading aperture width x height:	700 x 470 mm
Bale length x Bale width x Bale height:	700 x 500 x 600 mm
Bale weight:	60 kg
Width x Depth x Height:	1020 x 812 x 1922 mm
Weight:	290 kg
Related product line:	V-Press
Type of consumables:	Strapping tape
Press material:	Plastic film, Mixed paper, Cardboard

Product information



Bale removal and transport with discharge trolley



HSM TCS (Torsion Control System) for monitoring press ram movement



Modern microprocessor controller with membrane keypad and text display




Compresses cardboard and film

Suitable for cardboard as well as film.



Automatic start

Automatic start of the pressing process after closing the door.



Optimized pressing

Massive press ram and extremely robust press plate guidance.



Double door

To fill the press, the upper half of the doors is swung to the right.



Bell-crank lever

Bell-crank lever for quick and safe opening of the door.



Strapping

Manual bale strapping with continuous polyester tape.

Made in Germany | cost effective | simple operation | 95% volume reduction

www.tuev-sued.de/ps-zert

www.hsm.eu